

BEST AVAILABLE COPY

PUB-NO: WO009920463A1

DOCUMENT-IDENTIFIER: WO 9920463 A1

TITLE: AROMATIC POLYAMIDE FILM AND MAGNETIC RECODING
MEDIA MADE
BY USING THE SAME

PUBN-DATE: April 29, 1999

INVENTOR-INFORMATION:

| NAME | COUNTRY |
|---------------------|---------|
| SUEOKA, MASANORI | JP |
| HORIUCHI, MITSUHIRO | JP |
| TSUKUDA, AKIMITSU | JP |

ASSIGNEE-INFORMATION:

| NAME | COUNTRY |
|--------------------|---------|
| TORAY INDUSTRIES | JP |
| SUEOKA MASANORI | JP |
| HORIUCHI MITSUHIRO | JP |
| TSUKUDA AKIMITSU | JP |

APPL-NO: JP09804748

APPL-DATE: October 20, 1998

PRIORITY-DATA: JP29004797A (October 22, 1997)

INT-CL (IPC): B32B027/34, B32B033/00 , G11B005/704

EUR-CL (EPC): B32B027/06

ABSTRACT:

An aromatic polyamide film, which is a laminated film comprising at least two layers characterized in that at least one outermost layer (A) of the film

is one made from a mixture comprising an aromatic polyamide and one or more other polymers, has a content of the other polymers of 0.1 to 10 wt.%, and satisfies the relationships: $0.01 \leq t/d \leq 0.5$, $0.05 \leq s/L \leq 1$ (wherein d represents the thickness (μm) of the layer (A); t represents the diameter (μm) of the equivalent circle of the other polymers; and L and s represent the major and minor axes (μm) thereof, respectively). The film is free from creasing and telescoping in the wind-up step and is excellent in surface wear resistance, thus being particularly useful as a high-productivity base film for magnetic recording media.